

PRE3206 External IP66 Twilight Switch

Prefect Product File



Key features.

- SUPPLY VOLTAGE 220-240 Volts AC 50 Hz
- LOAD: 10A incandescent, 6A fluorescent, 3A compact fluorescent, 3A low energy, 3A low voltage (switching primary of transformer) Max 6 fluorescent fittings, For fluorescent lighting total power factor correction compliance must not exceed 40µF, switch SON lighting via an appropriately rated contactor
- TIME OUT PERIOD Adjustable 1 hour to 16 hours or AUTO OFF.
- LIGHT LEVEL Adjustment 10 LUX to 1000 LUX approximately.
- TERMINAL CAPACITY 2.5mm²
- IP RATING IP 66
- MATERIAL Polystyrene
- TYPE Class 2
- TEMPERATURE -10°C to 35°C
- CONFORMITY EMC-89/336/EEC

The PRE3206 twilight switch will turn lighting on when the ambient light falls below a preset level. The lighting will then be turned off either when the light exceeds the preset level or after a preset time delay.

For example, the PRE3206 can be used to switch external security lights at night or to turn on display or sign lighting. The unit has a highly accurate adjustable photocell, a selectable time delay, adjustable switching differential and is mounted in a vandal resistant IP66 enclosure.



Prefect Controls specialize in the automatic control of heating, lighting, and ventilation systems. We offer simple, energy efficient solutions which will save money on heating and lighting in new buildings and in existing properties. Why pay higher gas and electricity bills than you need to? **Call us to see how we could help you to cut your energy costs by up to 50%**

For further details contact **Glen Golding** on: 01787 320 604

Cleverly simple control of energy...

Prefect Controls Ltd Unit 2, Church Field Business Park, Church Field Road, Sudbury, Suffolk, CO10 2YF
 Tel: 01787 320 604 Fax: 0845 450 3020 Email: mail@prefectcontrols.com Website: www.prefectcontrols.com
 Due to our policy of continuous improvement, we reserve the right to change specifications without notice

RoHS Compliant

